

Article Number: 597-00030

Caution Write-On Self-Laminating Tag, Fiber Optic Cable, 3.5" X 2.0", Orange, 25/pkg



### Base Data

Local Order Number CT2003X2

Type CT2003

Color Orange (OG)

**Features and Benefits**

- Clear laminating plastic flap permanently protects the writing and data marked on the tag.
- Mounting holes for easy mounting using standard cable ties.
- Markers can be mounted in any direction, either vertically, horizontally, as a wrap-around identification plate or as a flag for the best visual position on the cable assembly.

Color Marking Field Orange (OG)

Color of Print Black (BK)

**Product Description** HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

#### Product Features

- Easily and conveniently fits in a pants or shirt pocket.
- Once loaded, unit allows minimal label exposure to dust and moisture.
- Can be used with standard ball point pens or HellermannTyton nylon marking pens.
- Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit.
- The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling.

**Short Description** Caution Write-On Self-Laminating Tag, Fiber Optic Cable, 3.5" X2.0", Orange, 25/pkg

### Product Dimensions

Length L (imperial) 2.0 "

Length L (metric) 50.8 mm

Width W (imperial) 3.5 "

Width W (metric) 88.9 mm

Height H (imperial) 2.0 "

Height H (metric) 50.8 mm

Horizontal Repeat HR (metric) 88.90 mm

Horizontal Repeat HR (imperial) 3.5 "

Vertical Repeat VR (imperial) 2.0 "

Vertical Repeat VR (metric) 50.8 mm

### Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 25

Package Quantity 25

**Labels per Column** 1  
**Labels per Row** 1  
**Labels per Sheet** 1  
**Weight (Metric)** 0.2 kg

---

## Material and Specifications

**Material** Polyvinylchloride (PVC)  
**Material Shortcut** PVC  
**Operating Temperature** -40 °F to +266 °F (-40 °C to +130 °C)  
**ROHS Conformity** Yes