HellermannTyton

CTA0753X2



Article Number: 597-00035

Self-Laminating Tag, Adhesive Generic Write-On, Blank Lines, 3.0" X .75", Orange, 25/pkg

Base Data

Local Order Number CTA0753X2

Type CTA0753

Color Orange (OG)

- Features and Benefits Clear laminating plastic flap permanently protects the writing and data marked on the tag.
 - · Mounting holes for easy mounting using standard cable ties.
 - · Markers can be mounted in any direction, either vertically, horizontally, as a wrap-around identification plate or as a flag for the best visual position on the cable assembly.

Color Marking Field Orange (OG)

Color of Print Black (BK)

Product Description HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The selflaminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

Product Features

- Easily and conveniently fits in a pants or shirt pocket.
- Once loaded, unit allows minimal label exposure to dust and moisture.
- Can be used with standard ball point pens or HellermannTyton nylon marking pens.
- Excess liner is easily cut-off by tearing it over the edge guide at the front of the unit.
- The dispenser can be reloaded over and over again, making it a cost-effective and efficient method of labeling.

Short Description Self-Laminating Tag, Adhesive Generic Write-On, Blank Lines, 3.0" X.75", Orange, 25/pkg

Product Dimensions

Length L (imperial) 0.75 "

Length L (metric) 19.05 mm

Width W (imperial) 3.0 "

Width W (metric) 76.2 mm

Height H (imperial) 0.75 "

Height H (metric) 19.05 mm

Logistics and Packaging

Quantity per pack

Package Quantity (imperial) 25

Package Quantity 25

Labels per Column 1

Labels per Row 1

Labels per Sheet 1

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Operating Temperature $\,$ -40 °F to +266 °F (-40 °C to +130 °C)

ROHS Conformity Yes

© HellermannTyton 2014