




CTN10STD



**Article Number:** 169-60001

**Convoluted Tubing, Slit, 1.0" Diameter, PA6, Black w/Gray Stripe, 300ft/pkg**

 **RoHS**



[Download drawing](#)

Base Data

<b>Local Order Number</b>	CTN10STD
<b>Type</b>	CTN10
<b>Color</b>	Black with Gray Stripe (BKSTGY)
<b>Features and Benefits</b>	<ul style="list-style-type: none"><li>• Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture</li><li>• Tubing protects cables and wires against automotive fluids, vibration wear</li><li>• Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight</li></ul>
<b>Product Description</b>	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
<b>Short Description</b>	Convoluted Tubing, Slit, 1.0" Diameter, PA6, Black w/Gray Stripe, 300ft/pkg

Product Dimensions

<b>Length L (imperial)</b>	300.0 ft
<b>Length L (metric)</b>	91.44 mm
<b>Diameter D (imperial)</b>	1.32 "
<b>Diameter D (metric)</b>	33.53 mm
<b>Diameter D2 (imperial)</b>	1.06 "
<b>Diameter D2 (metric)</b>	26.92 mm
<b>Nominal Diameter (imperial)</b>	1 "
<b>Nominal Diameter (metric)</b>	25.4 mm
<b>Wall Thickness WT (imperial)</b>	0.005 "
<b>Wall Thickness WT (metric)</b>	0.127 mm

Logistics and Packaging

<b>Quantity per</b>	carton
<b>Package Quantity (imperial)</b>	300.0 ft
<b>Package Quantity</b>	91.44 m
<b>Carton Quantity</b>	300

Material and Specifications

<b>Material</b>	Polyamide 6 (PA6)
<b>Material Shortcut</b>	PA6
<b>Operating Temperature</b>	-40°F to +300°F (-40°C to +149°C)

