



CTP120



**Article Number:** 169-60506

**Convoluted Tubing, Slit, 0.5" Diameter, PE, Black, 8500ft/pkg**

 **RoHS**

Base Data

Local Order Number	CTP120
Type	CTP120
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install</li><li>• Tubing provides full coverage where spiral wrap or other coverings may not be suitable</li><li>• In harsh applications the tubing can provide resistance to crushing, impact, and abrasion</li><li>• Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires</li></ul>
Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, 0.5" Diameter, PE, Black, 8500ft/pkg

Product Dimensions

Length L (imperial)	8500.0 ft
Length L (metric)	2590.8 m
Diameter D (imperial)	0.7 "
Diameter D (metric)	17.78 mm
Diameter D2 (imperial)	0.52 "
Diameter D2 (metric)	13.11 mm
Nominal Diameter (imperial)	1/2 "
Nominal Diameter (metric)	12.7 mm
Wall Thickness WT (imperial)	0.005 "
Wall Thickness WT (metric)	0.127 mm

Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	8500 ft
Carton Quantity	8500

Material and Specifications

Material	Polyethylene (PE)
Material Shortcut	PE
Operating Temperature	-40°F to +199°F (-40°C to +93°C)
ROHS Conformity	Yes

