



CTP340



Article Number: 169-60512

Convoluted Tubing, Slit, 0.75" Diameter, PE, Black, 4200ft/pkg

 **RoHS**

Base Data

Local Order Number	CTP340
Type	CTP340
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.• Tubing provides full coverage where spiral wrap or other coverings may not be suitable.• In harsh applications the tubing provides resistance to crushing, impact, and abrasion.• Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.
Product Description	HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
Short Description	Convoluted Tubing, Slit, 0.75" Diameter, PE, Black, 4200ft/pkg

Product Dimensions

Length L (imperial)	4200.0 ft
Length L (metric)	1280.16 m
Diameter D (imperial)	0.989 "
Diameter D (metric)	25.12 mm
Diameter D2 (imperial)	0.76 "
Diameter D2 (metric)	19.28 mm
Nominal Diameter (imperial)	3/4 "
Nominal Diameter (metric)	19.05 mm
Wall Thickness WT (imperial)	0.005 "
Wall Thickness WT (metric)	0.127 mm

Logistics and Packaging

Quantity per	carton
Package Quantity (imperial)	4200 ft
Package Quantity	1280 m
Carton Quantity	4200

Material and Specifications

Material	Polyethylene (PE)
Material Shortcut	PE
Operating Temperature	-40°F to +199°F (-40°C to +93°C)

