

CTP380



Article Number: 169-60514

Convoluted Tubing, Slit, .375" Diameter, PE, Black, 15000ft/pkg



Base Data

Local Order Number CTP380

Type CTP380

Color Black (BK)

- Features and Benefits**
- Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install.
 - Tubing provides full coverage where spiral wrap or other coverings may not be suitable.
 - In harsh applications the tubing provides resistance to crushing, impact, and abrasion.
 - Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires.

Product Description HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offers excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

Short Description Convoluted Tubing, Slit, .375" Diameter, PE, Black, 15000ft/pkg

Product Dimensions

Length L (imperial) 15000.0 ft

Length L (metric) 4572.0 m

Diameter D (imperial) 0.526 "

Diameter D (metric) 13.36 mm

Diameter D2 (imperial) 0.38 "

Diameter D2 (metric) 9.652 mm

Nominal Diameter (imperial) 3/8 "

Nominal Diameter (metric) 9.652 mm

Wall Thickness WT (imperial) 0.005 "

Wall Thickness WT (metric) 0.127 mm

Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 15000.0 ft

Package Quantity 4572 m

Carton Quantity 15000

Material and Specifications

Material Polyethylene (PE)

Material Shortcut PE

Operating Temperature -40°F to +199°F (-40°C to +93°C)

ROHS Conformity Yes

© HellemannTyton 2014