

CTT60R0C2



Article Number: 112-56019

Compression Tie, 8" Long, 60lb Tensile Strength, PA66, Black, 100/pkg



Base Data

Local Order Number CTT60R0C2

Type CTT60R

Color Natural (NA)

Features and Benefits

- Head design contains clamping rails to provide full circumferential compression around bundles.
- Bent tail allows for quick insertion into head.

Product Description The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Compression Tie, 8" Long, 60lb Tensile Strength, PA66, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 60.0 lbs

Minimum Tensile Strength (N) 265.0 N

Length L (imperial) 8.0 "

Length L (metric) 205.0 mm

Width W (imperial) 0.19 "

Width W (metric) 4.7 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.8 "

Bundle Diameter max (metric) 45.0 mm

Thickness T (imperial) 0.05 "

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 5000 Pieces

Weight (Metric) 1.3 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes