

CTT60R0HIRHSM4



Article Number: 112-52111

Compression Tie, 8" Long, 60lb Tensile Strength, PA66HIRHS, Black, 1000/pkg



Base Data

Local Order Number CTT60R0HIRHSM4

Type CTT60R

Color Black (BK)

- Features and Benefits**
- High impact and heat stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.
 - Head design contains clamping rails to provide full circumferential compression around bundles.
 - Bent tail allows for quick insertion into head.

Product Description The 360 Degree compression ties were designed with upside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Compression Tie, 8" Long, 60lb Tensile Strength, PA66HIRHS, Black, 1000/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 60.0 lbs

Minimum Tensile Strength (N) 265.0 N

Length L (imperial) 8.0 "

Length L (metric) 205.0 mm

Width W (imperial) 0.19 "

Width W (metric) 4.7 mm

Bundle Diameter min (imperial) 0.06 "

Bundle Diameter min (metric) 1.5 mm

Bundle Diameter max (imperial) 1.8 "

Bundle Diameter max (metric) 45.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 1000

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut PA66HIRHS
CSA Certified No
Flammability UL94 HB
Operating Temperature -40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity Yes
UL Listed (US and Canada) No
UL Recognized (US and Canada) No
