

CTT60R0HIRM4



Article Number: 112-52109

Compression Tie, 8" Long, 60lb Tensile Strength, PA66HIRHS, Black, 1000/pkg

 RoHS

Base Data

Local Order Number	CTT60R0HIRM4
Type	CTT60R
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none">• High impact and heat stabilized cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.• Head design contains clamping rails to provide full circumferential compression around bundles.• Bent tail allows for quick insertion into head.
Product Description	The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Compression Tie, 8" Long, 60lb Tensile Strength, PA66HIRHS, Black, 1000/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	60.0 lbs
Minimum Tensile Strength (N)	265.0 N
Length L (imperial)	8.0 "
Length L (metric)	205.0 mm
Width W (imperial)	0.19 "
Width W (metric)	4.7 mm
Bundle Diameter min (imperial)	0.06 "
Bundle Diameter min (metric)	1.5 mm
Bundle Diameter max (imperial)	1.8 "
Bundle Diameter max (metric)	45.0 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	1000
Carton Quantity	5000

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
CSA Certified	No
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes
Certification / Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No