

CTT60R9M4



Article Number: 112-52106

Compression Tie, 8" Long, 60lb Tensile Strength, PA66, Natural, 1000/pkg

 RoHS

Base Data

|                               |                                                                                                                                                                                                                                                                                                                                                           |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Local Order Number            | CTT60R9M4                                                                                                                                                                                                                                                                                                                                                 |
| Type                          | CTT60R                                                                                                                                                                                                                                                                                                                                                    |
| Color                         | Natural (NA)                                                                                                                                                                                                                                                                                                                                              |
| Features and Benefits         | <ul style="list-style-type: none"><li>• Head design contains clamping rails to provide full circumferential compression around bundles.</li><li>• Bent tail allows for quick insertion into head.</li></ul>                                                                                                                                               |
| Product Description           | The 360 Degree compression ties were designed with underside clamping rails to allow for optimal surface contact and complete circumferential compression around the bundle. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| Fixation Method (FF)          | None                                                                                                                                                                                                                                                                                                                                                      |
| Identification Plate Position | none                                                                                                                                                                                                                                                                                                                                                      |
| Releasable Closure (Yes/No)   | No                                                                                                                                                                                                                                                                                                                                                        |
| Tie Closure                   | plastic pawl                                                                                                                                                                                                                                                                                                                                              |
| Variant                       | Inside Serrated                                                                                                                                                                                                                                                                                                                                           |
| Short Description             | Compression Tie, 8" Long, 60lb Tensile Strength, PA66, Natural, 1000/pkg                                                                                                                                                                                                                                                                                  |

Product Dimensions

|                                     |          |
|-------------------------------------|----------|
| Minimum Tensile Strength (imperial) | 60.0 lbs |
| Minimum Tensile Strength (N)        | 265.0 N  |
| Length L (imperial)                 | 8.0 "    |
| Length L (metric)                   | 205.0 mm |
| Width W (imperial)                  | 0.19 "   |
| Width W (metric)                    | 4.7 mm   |
| Bundle Diameter min (imperial)      | 0.06 "   |
| Bundle Diameter min (metric)        | 1.5 mm   |
| Bundle Diameter max (imperial)      | 1.8 "    |
| Bundle Diameter max (metric)        | 45.0 mm  |

Logistics and Packaging

|                  |      |
|------------------|------|
| Quantity per     | bag  |
| Package Quantity | 1000 |
| Carton Quantity  | 5000 |

Material and Specifications

|          |                      |
|----------|----------------------|
| Material | Polyamide 6.6 (PA66) |
|----------|----------------------|

**Material Shortcut** PA66

**CSA Certified** No

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes