

DCT110HIRK2

Article Number: 115-31100

Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 50/pkg



Base Data

Local Order Number DCT110HIRK2

Type DCT11

Color Black (BK)

- Features and Benefits**
- Provides dual separation between bundles to prevent chaffing and abrasion.
 - 150 lb. tensile strength ensures enough strength for heavy duty applications.
 - Straps are releasable for increased serviceability.

Product Description HellermannTyton's dual clamp ties are designed to provide parallel separation between hoses, wires, cables and tubing, protecting them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of tracks, trailers, and heavy duty equipment. The unique one-piece design features the dual head centered on the strap.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Dual Clamp Tie - 150.0 lb, Stud Dia .25", Length 19.2", Max Bun Dia 2.3", PA66HIRHS, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 150.0 lbs

Length L (imperial) 19.2 "

Length L (metric) 489.0 mm

Width W (imperial) 0.5 "

Width W (metric) 12.7 mm

Width W2 (imperial) 0.7 "

Width W2 (metric) 19.7 mm

Height H (imperial) 0.8 "

Height H (metric) 19.1 mm

Bundle Diameter min (imperial) 0.2 "

Bundle Diameter min (metric) 6.4 mm

Bundle Diameter max (imperial) 2.3 "

Bundle Diameter max (metric) 58.0 mm

Mounting Hole Diameter D (imperial) 0.2 "

Mounting Hole Diameter D (metric) 6.2 mm

Stud Size (Imperial) .25 "

Stud Size (Metric) 6.35 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	50
Carton Quantity	500 Pieces
Weight (Metric)	12 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Conformity	Yes