

DCT90HIRK2



Article Number: 115-30900

Dual Clamp Tie 150 lb, Length 13", Max Bun Dia 1.3", Width .5", PA66HIRHS, Black 50/pkg



Base Data

Local Order Number DCT90HIRK2

Type DCT9

Color Black (BK)

- Features and Benefits**
- Provides dual separation between bundles to prevent chaffing and abrasion.
 - 150 lb. tensile strength ensures enough strength for heavy duty applications.
 - Straps are releasable for increased serviceability.

Product Description HellermannTyton's dual clamp ties are designed to provide parallel separation between hoses, wires, cables and tubing, protecting them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of tracks, trailers, and heavy duty equipment. The unique one-piece design features the dual head centered on the strap.

Fixation Method (FF) Weld Stud Fixing

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Dual Clamp Tie 150 lb, Length 13", Max Bun Dia 1.3", Width .5", PA66HIRHS, Black 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 150.0 lbs

Length L (imperial) 13.0 "

Length L (metric) 331.0 mm

Width W (imperial) 0.5 "

Width W (metric) 12.7 mm

Height H (imperial) 0.8 "

Height H (metric) 19.3 mm

Bundle Diameter max (imperial) 1.3 "

Bundle Diameter max (metric) 33.0 mm

Stud Size (Imperial) 0.25 "

Stud Size (Metric) 6.35 mm

Logistics and Packaging

Quantity per bag

Package Quantity 50

Carton Quantity 400 Pieces

Weight (imperial) 0.5 lbs

Weight (Metric) 12 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40 °F to +230 °F (-40 °C to +110 °C)
ROHS Conformity	Yes