

DSWS50HSH1



Article Number: 151-06501

Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter .625"-6", Black, POM, PA66HS, 500/Pkg



Base Data

Local Order Number DSWS50HSH1

Type DSWS5

Color Black (BK)

Features and Benefits

- "H" profile of the saddles allows for broad surface contact with the bundle, which minimizes pinching and crushing of the bundle.
- Swivels in 360 degree motion to accommodate any area.
- Accommodates T50-T250 ties to handle both light duty and heavy duty applications.

Product Description These saddle spacers are installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate and prevent chafing and wear. The spacers can be easily rotated by hand, allowing the bundles to be crossed and rotated at any angle. Cable ties, which secure the bundles, are used with the spacers.

Fixation Method (FF) None

Short Description Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter .625"-6", Black, POM, PA66HS, 500/Pkg

Product Dimensions

Length L (imperial) 1.6 "

Length L (metric) 40.6 mm

Width W (imperial) 1.0 "

Width W (metric) 25.4 mm

Height H (imperial) 0.9 "

Height H (metric) 23.6 mm

Bundle Diameter min (imperial) 0.7 "

Bundle Diameter min (metric) 16.0 mm

Bundle Diameter max (imperial) 6.0 "

Bundle Diameter max (metric) 152.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 500

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Minimum Extraction Force (Imperial) 250.0 lbs

Minimum Extraction Force (Metric) 1112 N

Operating Temperature -40 °F to +221 °F (-40 °C to +105 °C)

ROHS Conformity Yes