

FCST



Article Number: 855-14203

ST Multimode Fiber Connector, 1/pkg

Base Data

Local Order Number FCST

Type FCST

- Features and Benefits**
- Use with epoxy or anaerobic adhesives for different applications or user preference.
 - Pre-radiused zirconia ceramic ferrules provide precision installation.
 - Meet ANSI/TIA/EIA 568-B standards.
 - Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements.

Connector Type ST

Product Description Our epoxy/anaerobic connectors are designed for field or factory installation, using either epoxy or anaerobic adhesives. These connectors are made with pre-radiused zirconia ceramic ferrules to provide precision alignment and installation.

Epoxy adhesives provide affordable and reliable connections with lowest losses (less than 0.5dB). The epoxy can be allowed to set overnight or cured in an inexpensive oven. Anaerobic adhesives can be used with accelerators for faster curing

Technical Description HellermannTyton offers ST multimode and single mode connectors. Designed for both field and factory installation using either epoxy or anaerobic adhesive.

Short Description ST Multimode Fiber Connector, 1/pkg

Product Dimensions

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 1

Package Quantity 1

Material and Specifications