

FEWM24



Article Number: 855-04208

Wall Mount Fiber Enclosure - Unloaded, accepts 4 Adapter Panels, 2 Splice Trays, Black, 1/pkg

Base Data

Local Order Number FEWM24

Type FEWM24

Color Black (BK)

- Features and Benefits**
- Durable stainless steel construction for long life.
 - Cable management spools for effective slack management.
 - Bend radius control to minimize hand and wrist strain.
 - Smooth grommet entry to protect cables from damage.
 - Locking tab for added security.
 - Meet ANSI/TIA/EIA 568-B standards.

Product Description HellermannTyton wall mount fiber enclosures provide a secure termination solution for applications requiring fully enclosed and/or lockable enclosures. Wall mount enclosures accommodate up to 144 fibers, mount easily and provide easy cable routing access behind the enclosure. Choose from enclosure options to accommodate 1, 2 or 4 standard LGX adapter panels.

Technical Description HellermannTyton wall mount fiber enclosures provide a secure termination solution for LAN applications requiring fully enclosed and/or lockable enclosures. Wall mount enclosures accommodate up to 144 fibers, mount easily and provide easy cable routing access behind the enclosure. Choose from enclosure options to accommodate 1, 2 or 4 standard LGX-style adapter panels.

Short Description Wall Mount Fiber Enclosure - Unloaded, accepts 4 Adapter Panels, 2 Splice Trays, Black, 1/pkg

Product Dimensions

Length L (imperial) 3.5 "

Length L (metric) 88.9 mm

Width W (imperial) 15.0 "

Width W (metric) 381.0 mm

Height H (imperial) 15.63 "

Height H (metric) 397.0 mm

Depth D (imperial) 3.7 "

Depth D (metric) 93.98 mm

Logistics and Packaging

Quantity per box

Package Quantity (imperial) 1

Package Quantity 1

Carton Quantity 1

Material and Specifications

Material Metal

Material Shortcut Metal

