

## GT.50X6MP2V2

Article Number: 854-44352

Grip Tie, 6"0.0"x.5", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg



### Base Data

Local Order Number GT.50X6MP2V2

Type GT.50X6

Color Maroon (MN)

- Features and Benefits**
- UL94V0-2 flame rate material allow use in air handling spaces.
  - Features quick release for repetitive access to cable and wire.
  - Can be opened and closed numerous times without failure.
  - Adjustable so one size can accommodate multiple bundle sizes.

**Product Description** The Grip Tie is a low profile, one piece fastening device. Constructed of a hook and loop design, laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.

**Short Description** Grip Tie, 6"0.0"x.5", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg

### Product Dimensions

Minimum Tensile Strength (imperial) 40.0 lbs

Minimum Tensile Strength (N) 177.93 N

Length L (imperial) 6.0 "

Length L (metric) 152.4 mm

Length L2 (imperial) 1.5 "

Length L2 (metric) 38.1 mm

Width W (imperial) 0.5 "

Width W (metric) 12.7 mm

Width W2 (imperial) 1.0 "

Width W2 (metric) 25.4 mm

Bundle Diameter max (imperial) 1.0 "

Bundle Diameter max (metric) 25.4 mm

### Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 10

Package Quantity 10

Carton Quantity 1000

### Material and Specifications

**Material** Polyamide (PA)  
Polypropylene (PP)

**Material Shortcut** PP

