

GT.50X8MP2V2



Article Number: 854-44368

Grip Tie, 8.0"x.5", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg

Base Data

Local Order Number GT.50X8MP2V2

Type GT.50X8

Color Maroon (MN)

- Features and Benefits**
- UL94V0-2 flame rate material allow use in air handling spaces.
 - Features quick release for repetitive access to cable and wire.
 - Can be opened and closed numerous times without failure.
 - Adjustable so one size can accommodate multiple bundle sizes.

Product Description The Grip Tie is a low profile, one piece fastening device. Constructed of polyethylene hook and nylon loop and laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords.

Short Description Grip Tie, 8.0"x.5", UL94V-2 Flame Rated, Polyamide; Polypropylene, Maroon, 10/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 40.0 lbs

Minimum Tensile Strength (N) 177.93 N

Length L (imperial) 8.0 "

Length L (metric) 203.2 mm

Length L2 (imperial) 1.5 "

Length L2 (metric) 38.1 mm

Width W (imperial) 0.5 "

Width W (metric) 12.7 mm

Width W2 (imperial) 1.0 "

Width W2 (metric) 25.4 mm

Bundle Diameter max (imperial) 1.91 "

Bundle Diameter max (metric) 48.514 mm

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 10

Package Quantity 10

Carton Quantity 1000

Material and Specifications

Material Polyamide 6 (PA6)
Polypropylene (PP)

