

## HDM250HIRH4



**Article Number:** 151-00438

**Standard Torque Mount, Mounting Hole 0.25", Max Torque 115.0 lb - in, PA66HIRHS, Black, 500/pkg**



### Base Data

**Local Order Number** HDM250HIRH4

**Type** HDM25

**Color** Black (BK)

- Features and Benefits**
- Mount and tie combination makes it easy to service bundles in the field.
  - Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
  - Eliminates the needs for multiple sized fix diameter clamps.

**Product Description** This mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

**Fixation Method (FF)** Screw Mounting and Rivet

**Short Description** Standard Torque Mount, Mounting Hole 0.25", Max Torque 115.0 lb - in, PA66HIRHS, Black, 500/pkg

### Product Dimensions

**Length L (imperial)** 1.4 "

**Length L (metric)** 35.8 mm

**Width W (imperial)** 0.75 "

**Width W (metric)** 19.0 mm

**Cable Tie Width Max (imperial)** 0.5 "

**Cable Tie Width max. (metric)** 12.7 mm

**Width W2 (imperial)** 0.52 "

**Width W2 (metric)** 13.3 mm

**Height H (imperial)** 0.66 "

**Height H (metric)** 16.7 mm

**Height H2 (imperial)** 0.31 "

**Height H2 (metric)** 8.0 mm

**Mounting Hole Diameter D (imperial)** 0.25 "

**Mounting Hole Diameter D (metric)** 6.2 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 500

**Carton Quantity** 4000

### Material and Specifications

**Material** Polyamide 6.6 high impact modified (PA66HIR)

**Material Shortcut** PA66HIRHSUV

<b>Flammability</b>	UL94 HB
<b>Maximum Torque (kgf-cm)</b>	132.5 kgf-cm
<b>Maximum Torque (lbf-ft)</b>	9.583 lbf-ft
<b>Operating Temperature</b>	-40 °F to +230 °F (-40 °C to +110 °C)
<b>ROHS Conformity</b>	Yes