

## HDM321HIHSUVH4



Article Number: 151-07100

Medium Torque Mount, Mounting .3125", Max Torque 40.0 lb - ft, PA66HIRHS, Black, 500/pkg



### Base Data

Local Order Number HDM321HIHSUVH4

Type HDM321

Color Black (BK)

**Features and Benefits**

- Mount and tie combination makes it easy to service bundles in the field.
- Made from impact modified, heat stabilized, UV resistant material, ideal for heavy duty environments.
- Eliminates the needs for multiple sized fix diameter clamps.

**Product Description** This heavy duty mount, when used with a cable tie eliminates the need to carry multiple sizes of fixed bundle diameter clamps; which reduces inventory and purchasing costs while simplifying the assembly process.

**Fixation Method (FF)** Screw Mounting and Rivet

**Short Description** Medium Torque Mount, Mounting .3125", Max Torque 40.0 lb - ft, PA66HIRHS, Black, 500/pkg

### Product Dimensions

Length L (imperial) 1.8 "

Length L (metric) 46.0 mm

Width W (imperial) 0.96 "

Width W (metric) 24.0 mm

Cable Tie Width Max (imperial) 0.5 "

Cable Tie Width max. (metric) 12.7 mm

Mounting Hole Diameter D (imperial) 0.3125 "

Mounting Hole Diameter D (metric) 8.31 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 500

### Material and Specifications

**Material** Polyamide 6.6 heat and UV stabilized (PA66HSUV)

**Material Shortcut** PA66HSUV

**Flammability** UL94 V2

**Maximum Torque (kgf-cm)** 553 kgf-cm

**Maximum Torque (lbf-ft)** 40 lbf-ft

**Operating Temperature** -40 °F to +221 °F (-40 °C to +105 °C)

**ROHS Conformity** Yes

