

IMP2.510C2



Article Number: 151-42259

IMP Plate, 2.5" X .75", Nylon, White, 100/pkg

RoHS

Base Data

Local Order Number	IMP2.510C2
Type	IMP2.5
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"><li>• Identification Marker Plates can be marked with a permanent pen, printed labels or hot stamped for a wide variety of labeling options.</li><li>• Any size bundle diameter can be marked because it is only dependent upon the length of the cable tie selected, provided the cable tie width does not exceed .29".</li><li>• The marker plates are stamped from nylon, making them a durable and long term method of identification. The mounting holes allow the marker to be mounted as a flag, tag or wrapped around the cable or bundle for a wide variety of installed positions.</li></ul>
Product Description	Identification Marker Plates can be mounted in any direction, either vertically or horizontally as flags, tags or wraparound identification plates. They can be marked with HellermannTyton marking pens (T82-R or T82-S), thermal transfer or laser labels or hot stamped. The markers are manufactured from nylon and are white in color.
Identification Plate Position	attached to bundle
Mounting method Identification ETIM	Others
Recommended Labels	TAG27T1-822
Variant	Other
Short Description	IMP Plate, 2.5" X .75", Nylon, White, 100/pkg
With label space ETIM	Yes

Product Dimensions

Length L (imperial)	2.5 "
Length L (metric)	63.5 mm
Length L2 (imperial)	2.03 "
Length L2 (metric)	51.56 mm
Width W (imperial)	0.75 "
Width W (metric)	19.05 mm
Cable Tie Width Max (imperial)	0.18 "
Cable Tie Width max. (metric)	4.80 mm
Thickness T (imperial)	0.016 "
Thickness T (Metric)	0.4

Logistics and Packaging

Quantity per	bag
Package Quantity (imperial)	100
Package Quantity	100
Carton Quantity	100 Pieces

**Weight (Metric)** 0.55 kg

**Material and Specifications**

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes