

## ISO4X250H1



Article Number: 151-00455

Isolator Mount for separating 0.25" tubing, Max Bundle Diameter 0.25", TPV, Black, 500/pkg



### Base Data

Local Order Number ISO4X250H1

Type ISO4X250

Color Black (BK)

- Features and Benefits**
- Design provides quick and easy assembly.
  - Isolator mount dampens harmful vibrations on bundles
  - Material is durable, chemical and abrasion resistant, and remains flexible in low temperatures.

**Product Description** HellermannTyton's isolator mount is used to align and separate 1/4" tubing or brake lines. Easy to assemble, the isolator dampens vibrations and can be used with up to four brake lines. Mounting the isolator can be accomplished with HellermannTyton's standard cable ties, button head ties and any of HellermannTyton's heavy equipment mounts. Mounting is optional, but recommended for long runs. The isolator is durable, chemical and abrasion resistant, and remains flexible in low temperatures.

**Short Description** Isolator Mount for separating 0.25" tubing, Max Bundle Diameter 0.25", TPV, Black, 500/pkg

### Product Dimensions

Width W (imperial) 0.9 "

Width W (metric) 23.4 mm

Bundle Diameter max (imperial) 0.25 "

Bundle Diameter max (metric) 6.4 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 500

### Material and Specifications

**Material** Thermoplastic vulcanized (TPV) rubber

**Material Shortcut** TPV

**Flammability** UL94 HB

**Operating Temperature** -110 °F to +347 °F (-79 °C to +175 °C)

**ROHS Conformity** Yes