

Article Number: 111-81815

Identification Tie, 3.9" Long, 18lb Tensile Strength, PA66, White, 100/pkg



Base Data

Local Order Number IT18R10C2

Type IT18R

Color White (WH)

- Features and Benefits**
- Identification plate feature allows bundles to be easily marked and identified.
 - Wire and cable harnesses can be secured and identified using just one product, which saves time.
 - Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.

Product Description HellermannTyton Identification cable ties feature an identification plate allowing wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.

Fixation Method (FF) None

Identification Plate Position attached to bundle

Mounting method Identification ETIM Others

Recommended Labels TAG16T3-822

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Identification Tie, 3.9" Long, 18lb Tensile Strength, PA66, White, 100/pkg

With label space ETIM Yes

Product Dimensions

Minimum Tensile Strength (imperial) 18.0 lbs

Minimum Tensile Strength (N) 80.0 N

Length L (imperial) 3.9 "

Length L (metric) 100.0 mm

Core diameter from / to 6.00 - 22.00 mm

Width W (imperial) 0.98 "

Width W (metric) 25.0 mm

Width W2 (imperial) 0.09 "

Width W2 (metric) 2.4 mm

Height H (imperial) 0.32 "

Height H (metric) 8.0 mm

Bundle Diameter min (imperial) 0.19 "

Bundle Diameter min (metric) 4.8 mm

Bundle Diameter max (imperial) 0.75 "

Bundle Diameter max (metric) 19.0 mm

Outside Diameter min. (imperial) 0.24 "

Outside Diameter min. (metric) 6.00 mm
Outside Diameter max. (imperial) 0.87 "
Outside Diameter max. (metric) 22.00 mm

Logistics and Packaging

Quantity per bag
Package Quantity 100
Carton Quantity 10000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
CSA Certified No
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes