

IT50RD2K3



Article Number: 111-85204

Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Red, 50/plain pkg



Base Data

Local Order Number IT50RD2K3

Type IT50RD

Color Red (RD)

- Features and Benefits**
- Identification plate feature allows bundles to be easily marked and identified.
 - Wire and cable harnesses can be secured and identified using just one product, which saves time.
 - Plates can be marked manually with a permanent marker or with a pre-printed adhesive label.

Product Description HellermannTyton Identification cable ties feature an identification plate allowing wire and cable bundles to be easily marked and identified. These ties enable wire and cables to be secured and identified using just one product, saving installation time. The plates can be marked using a permanent marker or with a HellermannTyton adhesive label.

Fixation Method (FF) None

Identification Plate Position attached to bundle

Mounting method Identification ETIM Others

Recommended Labels TAG15T3-822

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Identification Tie, 8" Long, 50lb Tensile Strength, PA66, Red, 50/plain pkg

With label space ETIM Yes

Product Dimensions

Minimum Tensile Strength (imperial) 50.0 lbs

Minimum Tensile Strength (N) 225.0 N

Length L (imperial) 8.0 "

Length L (metric) 205.0 mm

Core diameter from / to 10.00 - 44.00 mm

Width W (imperial) 1.1 "

Width W (metric) 29.0 mm

Width W2 (imperial) 0.19 "

Width W2 (metric) 4.7 mm

Height H (imperial) 1.04 "

Height H (metric) 26.3 mm

Bundle Diameter min (imperial) 0.4 "

Bundle Diameter min (metric) 10.0 mm

Bundle Diameter max (imperial) 1.7 "

Bundle Diameter max (metric) 44.0 mm

Outside Diameter min. (imperial) 0.393 "

Outside Diameter min. (metric) 10.00 mm
Outside Diameter max. (imperial) 1.73 "
Outside Diameter max. (metric) 44.00 mm

Logistics and Packaging

Quantity per bag
Package Quantity 50
Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
US MILSPEC MS3368-3-2C
CSA Certified No
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes