HellermannTyton

LTM2500C2

Article Number: 151-00358

Lashing Tie Mount, 0.73" x 1.5", 0.25" Screw, PA66HS, Black, 100/pkg



RoHS

Base Data

Local Order Number	LTM2500C2
Туре	LTM250
Color	Black (BK)
Features and Benefits	• The strap is parallel to the mount when inserted into the head, providing a mounting point for where the cable ties.
Product Description	The Lashing Tie Mount is designed to snap into the T250 lashing tie. The tie head is assembled perpendicular to the mount. The lashing tie mount is recommended for indoor or outdoor wall mount cable applications.
Fixation Method (FF)	Screw Mounting and Rivet
Short Description	Lashing Tie Mount, 0.73" x 1.5", 0.25" Screw, PA66HS, Black, 100/pkg

Product Dimensions

Length L (imperial)	1.5 "
Length L (metric)	37.1 mm
Width W (imperial)	0.73 "
Width W (metric)	18.5 mm
Cable Tie Width Max (imperial)	0.49 "
Cable Tie Width max. (metric)	12.5 mm
Height H (imperial)	0.38 "
Height H (metric)	9.6 mm
Mounting Hole Diameter D (imperial)	0.26 "
Mounting Hole Diameter D (metric)	6.6 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	100
Carton Quantity	3000

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40 °F to +221 °F (-40 °C to +105 °C)
ROHS Conformity	Yes