

MB30C2

Article Number: 151-00136

Screw Fastened Bases, .14" Max tie width, .12" Hole Dia., .75" Length/Width, PA66, Black, 100/pkg



Base Data

Local Order Number MB30C2

Type MB3

Color Black (BK)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
 - Secures with two or four screws, providing multiple options.
 - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Product Description HellermannTyton screw fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Fixation Method (FF) Screw Mounting and Rivet

Short Description Screw Fastened Bases, .14" Max tie width, .12" Hole Dia., .75" Length/Width, PA66, Black, 100/pkg

Product Dimensions

Length L (imperial) 0.75 "

Length L (metric) 19.0 mm

Width W (imperial) 0.75 "

Width W (metric) 19.0 mm

Cable Tie Width Max (imperial) 0.14 "

Cable Tie Width max. (metric) 3.6 mm

Height H (imperial) 0.15 "

Height H (metric) 3.8 mm

Mounting Hole Diameter D (imperial) 0.12 "

Mounting Hole Diameter D (metric) 3.0 mm

Mounting Hole Centers (imperial) 0.52 "

Mounting Hole Centers (metric) 13.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 12000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No

Flammability UL94 V2

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

Certification / Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes