

MB3A10A2C2

Article Number: 151-00331

Acrylic Adh. Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 100/pkg



Base Data

Local Order Number MB3A10A2C2

Type MB3A

Color White (WH)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
 - Secures with acrylic based adhesive backing for heavy bonding applications
 - Can also be secured using two or four screws; providing multiple options.
 - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Product Description HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Fixation Method (FF) Screw Mounting and Adhesive

Short Description Acrylic Adh. Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, White, 100/pkg

Product Dimensions

Length L (imperial) 0.75 "

Length L (metric) 19.0 mm

Width W (imperial) 0.75 "

Width W (metric) 19.0 mm

Cable Tie Width Max (imperial) 0.14 "

Cable Tie Width max. (metric) 3.6 mm

Height H (imperial) 0.19 "

Height H (metric) 4.8 mm

Mounting Hole Diameter D (imperial) 0.12 "

Mounting Hole Diameter D (metric) 3.0 mm

Mounting Hole Centers (imperial) 0.52 "

Mounting Hole Centers (metric) 13.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 10000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Acrylate with base of acrylic foam

Flammability UL94 V2 (excluding adhesive)

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes