

## MB4A10A2H4

Article Number: 151-00322

Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 500/pkg



### Base Data

Local Order Number MB4A10A2H4

Type MB4A

Color White (WH)

- Features and Benefits**
- For use with 18 and 50 pound cable ties to provide stability when securing bundles.
  - Secures with acrylic based adhesive backing for heavy bonding applications. Can also be secured using two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66, White, 500/pkg

### Product Dimensions

Length L (imperial) 1.12 "

Length L (metric) 28.5 mm

Width W (imperial) 1.12 "

Width W (metric) 28.5 mm

Cable Tie Width Max (imperial) 0.18 "

Cable Tie Width max. (metric) 4.6 mm

Height H (imperial) 0.23 "

Height H (metric) 5.8 mm

Mounting Hole Diameter D (imperial) 0.18 "

Mounting Hole Diameter D (metric) 4.6 mm

Mounting Hole Centers (imperial) 0.8 "

Mounting Hole Centers (metric) 20.2 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Acrylate with base of acrylic foam

**Flammability** UL94 V2 (excluding adhesive)  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes

---