

## MB4SHA0H4



Article Number: 151-29202

Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, Black, 500/pkg



### Base Data

Local Order Number MB4SHA0H4

Type MB4SHA

Color Black (BK)

**Features and Benefits**

- 2-way opening for use with 18 through 50 pound cable ties to provide stability when securing bundles.
- Secures using the adhesive backing and/or with one screw.

**Product Description** HellermannTyton's 2 way, adhesive fastened mounting base is used with 18 through 50 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by inserting one screw through the center of the mount.

**Fixation Method (FF)** Screw Mounting and Adhesive

**Short Description** Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, Black, 500/pkg

### Product Dimensions

Length L (imperial) 1.12 "

Length L (metric) 28.3 mm

Width W (imperial) 1.12 "

Width W (metric) 28.3 mm

Cable Tie Width Max (imperial) 0.18 "

Cable Tie Width max. (metric) 4.6 mm

Height H (imperial) 0.23 "

Height H (metric) 5.8 mm

Mounting Hole Diameter D (imperial) 0.15 "

Mounting Hole Diameter D (metric) 3.9 mm

Thickness of Adhesive TA (imperial) 0.031 "

Thickness of Adhesive TA (metric) 0.8 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 500

Carton Quantity 4000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Adhesive** Synthetic rubber with base of polyethylene foam

**Shortcut Adhesive** Synthetic rubber

**Adhesive Operating Temperature** -4 °F to +122 °F (-20°C to +50°C)  
**CSA Certified** No  
**Flammability** UL94 V2 (excluding adhesive)  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes