

MB4SHA10C2



Article Number: 151-29203

Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 100/pkg



Base Data

Local Order Number MB4SHA10C2

Type MB4SHA

Color White (WH)

Features and Benefits

- 2-way opening for use with 18 through 50 pound cable ties to provide stability when securing bundles.
- Secures using the adhesive backing and/or with one screw.

Product Description HellermannTyton's 2 way, adhesive fastened mounting base is used with 18 through 50 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by inserting one screw through the center of the mount.

Fixation Method (FF) Screw Mounting and Adhesive

Short Description Adhesive Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 100/pkg

Product Dimensions

Length L (imperial) 1.12 "

Length L (metric) 28.3 mm

Width W (imperial) 1.12 "

Width W (metric) 28.3 mm

Cable Tie Width Max (imperial) 0.18 "

Cable Tie Width max. (metric) 4.6 mm

Height H (imperial) 0.23 "

Height H (metric) 5.8 mm

Mounting Hole Diameter D (imperial) 0.15 "

Mounting Hole Diameter D (metric) 3.9 mm

Thickness of Adhesive TA (imperial) 0.031 "

Thickness of Adhesive TA (metric) 0.8 mm

Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 4000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Synthetic rubber with base of polyethylene foam

Shortcut Adhesive Synthetic rubber

Adhesive Operating Temperature -4 °F to +122 °F (-20°C to +50°C)
CSA Certified No
Flammability UL94 V2 (excluding adhesive)
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes