

## MB510F4



**Article Number:** 151-28504

**Screw Fastened Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 250/pkg**



### Base Data

**Local Order Number** MB510F4

**Type** MB5

**Color** White (WH)

- Features and Benefits**
- For use with 18 through 150 pound cable ties to provide stability when securing bundles.
  - Secures with two or four screws; for multiple options.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton screw fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Fixation Method (FF)** Screw Mounting and Rivet

**Short Description** Screw Fastened Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 250/pkg

### Product Dimensions

**Length L (imperial)** 1.49 "

**Length L (metric)** 37.7 mm

**Width W (imperial)** 1.49 "

**Width W (metric)** 37.7 mm

**Cable Tie Width Max (imperial)** 0.35 "

**Cable Tie Width max. (metric)** 8.9 mm

**Height H (imperial)** 0.25 "

**Height H (metric)** 6.2 mm

**Mounting Hole Diameter D (imperial)** 0.19 "

**Mounting Hole Diameter D (metric)** 4.8 mm

**Mounting Hole Centers (imperial)** 1.0 "

**Mounting Hole Centers (metric)** 25.3 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 250

**Carton Quantity** 3000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**CSA Certified** No

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes