

MB5A10F4



Article Number: 151-00427

Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 250/pkg

 RoHS

Base Data

Local Order Number	MB5A10F4
Type	MB5A
Color	White (WH)
Features and Benefits	• For use with 18 and 30 pound cable ties to provide stability when securing bundles. • Secures with rubber based adhesive backing and/or two or four screws. • 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.
Product Description	HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.
Fixation Method (FF)	Screw Mounting and Adhesive
Short Description	Adhesive Bases, .35" Max tie width, .19" Hole Dia., 1.49" Length/Width, PA66, White, 250/pkg

Product Dimensions

Length L (imperial)	1.49 "
Length L (metric)	37.7 mm
Width W (imperial)	1.49 "
Width W (metric)	37.7 mm
Cable Tie Width Max (imperial)	0.35 "
Cable Tie Width max. (metric)	8.9 mm
Height H (imperial)	0.28 "
Height H (metric)	7.1 mm
Mounting Hole Diameter D (imperial)	0.19 "
Mounting Hole Diameter D (metric)	4.8 mm
Mounting Hole Centers (imperial)	1.0 "
Mounting Hole Centers (metric)	25.3 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	250
Carton Quantity	2000

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No

Flammability UL94 V2 (excluding adhesive)

Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)

ROHS Conformity Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes