

MBT20H-S



Article Number: 111-94208

Stainless Steel Tie, 20.5" Long, 450lb Tensile Strength, SS304, Metal, 50/pkg



Base Data

Local Order Number MBT20H-S

Type MBT20HS

Color Metal (ML)

Features and Benefits

- 304 grade stainless steel offers excellent resistance to corrosion, weather and chemical resistance.
- Ball bearing locking mechanism assures high tensile strength and easy insertion.

Product Description HellermannTyton's stainless steel ties are designed with a ball bearing locking mechanism to assure high tensile strength and easy insertion when securing hoses, cables, pipes and more. Available in 304 or 316 grades of stainless steel, providing protection when used in corrosive environments, fire resistance and temperature extremes.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) No

Tie Closure ball bearing lock

Variant No Serration

Short Description Stainless Steel Tie, 20.5" Long, 450lb Tensile Strength, SS304, Metal, 50/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 450.0 lbs

Minimum Tensile Strength (N) 2000.0 N

Length L (imperial) 20.5 "

Length L (metric) 521.0 mm

Width W (imperial) 0.31 "

Width W (metric) 7.9 mm

Bundle Diameter min (imperial) 0.67 "

Bundle Diameter min (metric) 17.0 mm

Bundle Diameter max (imperial) 6.0 "

Bundle Diameter max (metric) 152.0 mm

Thickness T (imperial) 0.01 "

Thickness T (Metric) 0.3 mm

Logistics and Packaging

Quantity per bag

Package Quantity 50

Carton Quantity 1000 Pieces

Weight (Metric) 11.15 kg

Material and Specifications

Material	Stainless Steel (SS304)
Material Shortcut	SS304
Flammability	non-burning
Halogenfree	Yes
Operating Temperature	-112 °F to +1000 °F (-80 °C to +538 °C)
ROHS Conformity	Yes