HellermannTyton

MCRI-FE



Article Number: 250-00046

InfoStream Multi-Channel Raceway Flat Elbow, HIPS, Ivory, 1/pkg

RoHS

Base Data

Local Order Number MCRI-FE

Type MCR-FE

Color Ivory (IV)

Features and Benefits • Raceway and fittings are manufactured from a UL 94V-0 rated material to insure compliance with codes

 $\bullet \ \text{All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII fittings have been designed to meet TIA/EIA-568-B \ and 569-AII f$

standards

• Raceway and fittings are U.L. Listed to 600 Volts to meets new UL5A and CSA 22.2 No. 62-93 standards

• Patented hinged cover speeds installation time by allowing installer to partially mount cover prior to laying cables

Product Description HellermannTyton's InfoStream non-metallic raceway system can accommodate up to four separate channels of

electrical, voice, data, video or fiber optic cabling. The elliptical shape is aesthetically pleasing when compared to

other designs. The raceway's unique and patented design make installations quicker and easier.

Short Description InfoStream Multi-Channel Raceway Flat Elbow, HIPS, Ivory, 1/pkg

Product Dimensions

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 1

Package Quantity 1

Carton Quantity 25

Material and Specifications

Material Polystyrene, high impact resistant (PS-HIR)

Material Shortcut HIPS

ROHS Conformity Yes