HellermannTyton

MK9PUA



Article Number: 110-09112

Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings.

RoHS

Base Data

Local Order Number MK9PUA

Type MK9P

Features and Benefits The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in

demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties.

Like the MK7P, HellermannTyton's MK9P incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P features adjustable, easy to read

tension settings. Lock-out features are available.

The MK9P is available with lower air attachment (standard) or can be ordered with an upper air attachment.

Air Attachment upper air connection

Air Pressure Bar (min.) 3

Product Description The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in

demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties.

Number of cycles 1000000

Air Pressure PSI 9

Cable Tie Thickness max. 2.5 mm

Tension Setting Tools Adjustable

Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings.

Product Dimensions

Air Pressure Bar (max.) 6

Air Supply non lubricated / lubricated

Cycle Time 2 strokes per second

Cable Tie Width Max (imperial) 0.5

Cable Tie Width max. (metric) 12.7 mm

Hose Internal Diameter (metric) 4.0 mm

Pawl Travel Stroke (imperial) 1.25 "

Pawl Travel Stroke (metric) 3.175 cm

Power Supply Dry or lubricated air

Tension Force Adjustable

Logistics and Packaging

Quantity per carton

Package Quantity (imperial) 1

Package Quantity 1

Carton Quantity 1

Weight (imperial) 32 oz
Weight (Metric) 0.91 kg

Material and Specifications

ROHS Conformity Yes

© HellermannTyton 2014