



MSBT1200HIRHSH1



**Article Number:** 151-29301

**Saddle Mount For Button Head Tie, Mounting Hole Diameter 0.44" - 0.82", PA66HIRHSUV, Black, 500/pkg**

 **RoHS**

Base Data

Local Order Number	MSBT1200HIRHSH1
Type	MSBT120
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"><li>• Secures up to three bundles for multiple routing.</li><li>• Provides parallel spacing between frame rail and adjacent bundles to reduce wear.</li><li>• Manufactured with a pilot bushing which prevent the cable tie from chafing against the burr edge of the mounting hole.</li></ul>
Product Description	HellermannTyton's saddle mounts are designed to be used with HellermannTyton's button head ties, and stand off bundles from frame rails, providing clearance from bolts and other protrusions for protection against abrasion. This also allows the flow-through of salt, dirt, and other impurities from the road which prevent unwanted build-up on hoses and harnesses.
Short Description	Saddle Mount For Button Head Tie, Mounting Hole Diameter 0.44" - 0.82", PA66HIRHSUV, Black, 500/pkg

Product Dimensions

Length L (imperial)	1.9 "
Length L (metric)	48.3 mm
Bundle Diameter 2nd Loop max (imperial)	1.0 "
Width W (imperial)	0.65 "
Width W (metric)	16.5 mm
Height H (imperial)	0.8 "
Height H (metric)	20.6 mm
Height H2 (imperial)	0.9 "
Height H2 (metric)	22.2 mm
Panel Thickness min. (imperial)	0.16 "
Panel Thickness min. (metric)	4.1 mm
Mounting Hole Diameter D min (imperial)	0.44 "
Mounting Hole Diameter D max (imperial)	0.82 "
Bundle Diameter 1st Loop max (imperial)	6.0 "
Bundle Diameter 1st Loop max (metric)	152.4 mm
Mounting Hole Diameter D max (metric)	20.8 mm
Mounting Hole Diameter D min (metric)	11.2 mm
Bundle Diameter 2nd Loop max (metric)	25.4 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	500

Material and Specifications

---

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-65 °F to +230 °F (-54 °C to +110 °C)
ROHS Conformity	Yes