

## PBM10M4



**Article Number:** 151-00231

**Push Mount, .25" Hole Dia., .12" Max Panel, .2" Max Tie Width, PA66, White, 1000/pkg**



### Base Data

**Local Order Number** PBM10M4

**Type** PBM

**Color** White (WH)

- Features and Benefits**
- Push Mounts, when used with standard cable ties, provide a permanent bundling solution below a panel.
  - The "button" style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

**Product Description** HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for installation below or underneath a panel. Designed for simple installation by pushing the mount through a pre-drilled hole. The low profile "button" style head is suitable in space constrained areas.

**Short Description** Push Mount, .25" Hole Dia., .12" Max Panel, .2" Max Tie Width, PA66, White, 1000/pkg

### Product Dimensions

**Width W (imperial)** 0.26 "

**Width W (metric)** 6.6 mm

**Cable Tie Width Max (imperial)** 0.2 "

**Cable Tie Width max. (metric)** 5.0 mm

**Height H (imperial)** 0.4 "

**Height H (metric)** 10.2 mm

**Height H2 (imperial)** 0.08 "

**Height H2 (metric)** 2.0 mm

**Panel Thickness max. (imperial)** 0.12 "

**Panel Thickness max. (metric)** 3.0 mm

**Mounting Hole Diameter D (imperial)** 0.25 "

**Mounting Hole Diameter D (metric)** 6.35 mm

**Mounting Hole Diameter D max (imperial)** 0.29 "

**Mounting Hole Diameter D max (metric)** 6.4 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 1000

**Carton Quantity** 20000

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**CSA Certified** No

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes