

## PBM9C2

Article Number: 151-00232

Push Mount, .25" Hole Dia., .12" Max Panel, .2" Max Tie Width, PA66, Natural, 100/pkg



### Base Data

Local Order Number PBM9C2

Type PBM

Color Natural (NA)

**Features and Benefits**

- Push Mounts, when used with standard cable ties, provide a permanent bundling solution below a panel.
- The "button" style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

**Product Description** HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for installation below or underneath a panel. Designed for simple installation by pushing the mount through a pre-drilled hole. The low profile "button" style head is suitable in space constrained areas.

**Short Description** Push Mount, .25" Hole Dia., .12" Max Panel, .2" Max Tie Width, PA66, Natural, 100/pkg

### Product Dimensions

Width W (imperial) 0.26 "

Width W (metric) 6.6 mm

Cable Tie Width Max (imperial) 0.2 "

Cable Tie Width max. (metric) 5.0 mm

Height H (imperial) 0.4 "

Height H (metric) 10.2 mm

Height H2 (imperial) 0.08 "

Height H2 (metric) 2.0 mm

Panel Thickness max. (imperial) 0.12 "

Panel Thickness max. (metric) 3.0 mm

Mounting Hole Diameter D (imperial) 0.25 "

Mounting Hole Diameter D (metric) 6.35 mm

Mounting Hole Diameter D max (imperial) 0.29 "

Mounting Hole Diameter D max (metric) 6.4 mm

### Logistics and Packaging

Quantity per bag

Package Quantity 100

Carton Quantity 15000

### Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

CSA Certified No

**Flammability** UL94 V2

**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)

**ROHS Conformity** Yes

**Certification / Specification** UL

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes