HellermannTyton

PP24MOD6AS

Article Number: 853-55002

Category 6A - 1U 24 Port Shielded Patch Panel

HellermannTyton

Base Data

Local Order Number	PP24MOD6AS
Туре	PP24SMOD6ASCN
Features and Benefits	 Integral earthing plate grounds each keystone jack helping to guarantee 10G performance by giving continuity of the 360° shielding. Rear cable management incorporated in the panel.
Product Description	HellermannTyton's Category 6A shielded patch panels accept HellermannTyton Shielded Category 6A jacks* (RJ45FC6AS) to complete a shielded system solution. The panel provides a choice of ground stud positions on the integral grounding bar and includes rear cable management. Panels are offered in two styles, a fixed version or a sliding version to ease installation. *Jacks are ordered separately
Sub Category	Panel
Technical Description	The Deca10 copper solution is designed using S-FTP Cat6A cable which provides 360° shielding and eliminates alien crosstalk. The Deca10 Cat6A panel accommodates 24 Cat6A Keystone Jack allowing 24 Cat6A connections in 1U. The integral earthing plate grounds each Keystone Jack helping to guarantee 10G performance by giving continuity of the 360° shielding. Tested to exceed ISO/EIA 11801:2002 amendment 1.1 and ANSI/TIA/EIA 568 - C.2 standards, the Deca10 Cat6A panel offers backward compatibility with Cat6, Cat5E, Cat5 and voice products.
Short Description	Category 6A - 1U 24 Port Shielded Patch Panel

Product Dimensions

Width W (imperial)	19.0 "
Width W (metric)	483 mm
Height H (imperial)	1.7 "
Height H (metric)	44.0 mm

Logistics and Packaging

Package Quantity (imperial) 1

Package Quantity 1

Material and Specifications

© HellermannTyton 2014