

PR1M4



Article Number: 181-00139

Panel Rivet, PA66, Natural, 1000/pkg



Base Data

Local Order Number PR1M4

Type PR1

Color Natural (NA)

Features and Benefits

- Nylon material holds duct securely to panel
- Non-metallic rivet will not corrode; ensuring longevity

Product Description HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".

Short Description Panel Rivet, PA66, Natural, 1000/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 107.0 lbs

Minimum Tensile Strength (N) 478 N

Panel Thickness max. (imperial) 0.28 "

Panel Thickness max. (metric) 7.00 mm

Panel Thickness min. (imperial) 0.15 "

Panel Thickness min. (metric) 3.90 mm

Mounting Hole Diameter D (imperial) 0.2 "

Mounting Hole Diameter D (metric) 5.0 mm

Diameter max. (imperial) 0.02 "

Diameter max. (metric) 0.51 mm

Logistics and Packaging

Quantity per bag

Package Quantity (imperial) 1000

Package Quantity 1000

Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA6

Flammability UL94 V2

Operating Temperature -40°F to +176°F (-40°C to +80°C)

ROHS Conformity Yes

Certification/Specification IMQ

