

## REZ200.NB3P



**Article Number:** 115-40200

**Releasable Cable Tie, 7.9" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg**



### Base Data

**Local Order Number** REZ200.NB3P

**Type** REZ200

**Color** Black (BK)

**Features and Benefits**

- The unique, patented head design enables the tie to be inserted through a standard style head for permanent locking or can be twisted into the pinch-releasable style head for easy opening at a later time.
- The quick pinch-release mechanism can be released by one hand even when the tie is under tension.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** Yes

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Releasable Cable Tie, 7.9" Long, 30 lb Tensile Strength, PA66, Black, 100/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 30.0 lbs

**Minimum Tensile Strength (N)** 135 N

**Length L (imperial)** 7.9 "

**Length L (metric)** 200 mm

**Width W (imperial)** 0.19 "

**Width W (metric)** 4.7 mm

**Bundle Diameter min (imperial)** 0.63 "

**Bundle Diameter min (metric)** 16.0 mm

**Bundle Diameter max (imperial)** 2.0 "

**Bundle Diameter max (metric)** 50.0 mm

**Thickness T (imperial)** 0.055 "

**Thickness T (Metric)** 1.4 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 100

**Carton Quantity** 6000 Pieces

**Weight (Metric)** 1.76 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes