

RO175WP

Article Number: 590-10000

Rite-On Self-Laminating Label Starter Kit, .75" X .75" X 3.0", Vinyl, White, 90/RL



Base Data

Local Order Number	RO175WP
Type	RO175WP
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • Compact to easily fit in pants or shirt pockets. • Dispenser can be reloaded over and over, making it cost effective to use. • Dispenser edge allows easy removal of label liner. • Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.
Color Marking Field	White (WH)
Product Description	HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.
Fixation Method (FF)	Pasting / Stick
Mounting method Identification ETIM	Pasting / Stick
Self adhesive (Yes/No)	Yes
Variant	Roller form
Short Description	Rite-On Self-Laminating Label Starter Kit, .75" X .75" X 3.0", Vinyl, White, 90/RL
With label space ETIM	Yes

Product Dimensions

Length L (imperial)	0.75 "
Length L (metric)	19.05 mm
Core diameter from / to	8.38 - 17.78 mm
Width W (imperial)	0.75 "
Width W (metric)	19.05 mm
Height H (imperial)	0.75 "
Height H (metric)	19.05 mm
Height H2 (imperial)	3.0 "
Height H2 (metric)	76.2 mm
Bundle Diameter min (imperial)	0.33 "
Bundle Diameter min (metric)	8.32 mm
Bundle Diameter max (imperial)	0.7 "
Bundle Diameter max (metric)	17.78 mm
Outside Diameter min. (imperial)	0.33 "
Outside Diameter min. (metric)	8.38 mm
Outside Diameter max. (imperial)	0.7 "

Outside Diameter max. (metric) 17.78 mm

Wire Size Range (AWG) 4 to 4/0

Logistics and Packaging

Quantity per EA

Package Quantity (imperial) 90

Package Quantity 90

Carton Quantity 1 Pieces

Material and Specifications

Material Type 100, self laminating Vinyl, white (WH)

Material Shortcut 100

Adhesive Acrylic

Shortcut Adhesive Acryl

Adhesive Operating Temperature -51 °F to +200 °F (-46 °C to +93 °C)

Operating Temperature -51 °F to +200 °F (-46 °C to +93 °C)

ROHS Conformity Yes