

RO512

Article Number: 590-05120

Rite-On Self-Laminating Label Dispenser, .75" X .5" X 1.875", Vinyl, White, 150/RL



Base Data

Local Order Number RO512

Type RO512

Color Transparent (CL)
White (WH)

- Features and Benefits**
- Compact to easily fit in pants or shirt pockets.
 - Dispenser can be reloaded over and over, making it cost effective to use.
 - Dispenser edge allows easy removal of label liner.
 - Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.

Color Marking Field White (WH)

Product Description HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

Fixation Method (FF) Pasting / Stick

Mounting method Identification ETIM Pasting / Stick

Self adhesive (Yes/No) Yes

Variant Roller form

Short Description Rite-On Self-Laminating Label Dispenser, .75" X .5" X 1.875", Vinyl, White, 150/RL

With label space ETIM Yes

Product Dimensions

Length L (imperial) 0.5 "

Length L (metric) 12.7 mm

Core diameter from / to 6.68 - 8.38 mm

Width W (imperial) 0.75 "

Width W (metric) 19.05 mm

Height H (imperial) 0.5 "

Height H (metric) 12.7 mm

Height H2 (imperial) 1.875 "

Height H2 (metric) 47.62 mm

Bundle Diameter min (imperial) 0.26 "

Bundle Diameter min (metric) 6.68 mm

Bundle Diameter max (imperial) 0.33 "

Bundle Diameter max (metric) 8.38 mm

Outside Diameter min. (imperial) 0.263 "

Outside Diameter min. (metric) 6.68 mm

Outside Diameter max. (imperial) 0.33 "
Outside Diameter max. (metric) 8.38 mm
Wire Size Range (AWG) 8 to 4 AWG

Logistics and Packaging

Quantity per pack
Package Quantity (imperial) 150
Package Quantity 150
Carton Quantity 1

Material and Specifications

Material Type 100, self laminating Vinyl, white (WH)
Material Shortcut 100
Shortcut Adhesive Acryl
Adhesive Operating Temperature -51 °F to +200 °F (-46 °C to +93 °C)
Operating Temperature -51 °F to +200 °F (-46 °C to +93 °C)
ROHS Conformity Yes