

RO514

Article Number: 590-05140

Rite-On Self-Laminating Label Dispenser, .75" X .375" X 1.25", Vinyl, White, 200/RL



Base Data

Local Order Number RO514

Type RO514

Color White (WH)

- Features and Benefits**
- Compact to easily fit in pants or shirt pockets.
 - Dispenser can be reloaded over and over, making it cost effective to use.
 - Dispenser edge allows easy removal of label liner.
 - Dispenser protects labels from dirt and moisture before use, extending the life and quality of the labels.

Color Marking Field White (WH)

Product Description HellermannTyton's Rite-On Markers are made from a flexible vinyl film and used to mark wire and cable. The self-laminating labels have a clear tail which seals the legend under clear vinyl, maintaining the quality of the labels. The Rite-On markers are packaged in a reusable dispenser made from high impact plastic which is resistant to oils and grease.

Fixation Method (FF) Pasting / Stick

Mounting method Identification ETIM Pasting / Stick

Self adhesive (Yes/No) Yes

Variant Roller form

Short Description Rite-On Self-Laminating Label Dispenser, .75" X .375" X 1.25", Vinyl, White, 200/RL

With label space ETIM Yes

Product Dimensions

Length L (imperial) 0.375 "

Length L (metric) 9.52 mm

Core diameter from / to 3.89 - 6.68 mm

Width W (imperial) 0.75 "

Width W (metric) 19.05 mm

Height H (imperial) 0.375 "

Height H (metric) 9.52 mm

Height H2 (imperial) 1.25 "

Height H2 (metric) 31.75 mm

Bundle Diameter min (imperial) 0.15 "

Bundle Diameter min (metric) 3.89 mm

Bundle Diameter max (imperial) 0.263 "

Bundle Diameter max (metric) 6.68 mm

Outside Diameter min. (imperial) 0.153 "

Outside Diameter min. (metric) 3.89 mm

Outside Diameter max. (imperial) 0.263 "

Outside Diameter max. (metric) 6.68 mm

Wire Size Range (AWG) 14 to 8 AWG

Logistics and Packaging

Quantity per EA
Package Quantity (imperial) 200
Package Quantity 200
Carton Quantity 1
Weight (Metric) 0.1 kg

Material and Specifications

Material Type 100, self laminating Vinyl, white (WH)
Material Shortcut 100
Adhesive Acrylic
Shortcut Adhesive Acryl
Adhesive Operating Temperature -51 °F to +200 °F (-46 °C to +93 °C)
Operating Temperature -40 °F to +176 °F (-40 °C to +80 °C)
ROHS Conformity Yes