

## RT150LEP0X2



**Article Number:** 115-00038

**Releasable Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg**



### Base Data

**Local Order Number** RT150LEP0X2

**Type** RT150LEP

**Color** Black (BK)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
  - Head design provides high tensile strength with very low insertion force even after repeated use.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** Yes

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Releasable Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 175.0 lbs

**Minimum Tensile Strength (N)** 780.0 N

**Length L (imperial)** 32.3 "

**Length L (metric)** 820.0 mm

**Width W (imperial)** 0.35 "

**Width W (metric)** 8.8 mm

**Cable Tie Width Max (imperial)** 0.346 "

**Cable Tie Width max. (metric)** 8.8 mm

**Bundle Diameter min (imperial)** 0.32 "

**Bundle Diameter min (metric)** 8.0 mm

**Bundle Diameter max (imperial)** 9.6 "

**Bundle Diameter max (metric)** 245.0 mm

### Logistics and Packaging

**Quantity per** bag

**Package Quantity** 25

**Carton Quantity** 500

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes