HellermannTyton

RT150REP0X2



Article Number: 115-00036

Releasable Cable Tie, 15.4" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

RoHS

Base Data

Local Order Number RT150REP0X2

Type RT150REP

Color Black (BK)

Features and Benefits • Special design offers a release feature for quick and easy access to wire bundles.

· Head design provides high tensile strength with very low insertion force even after repeated use.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles

when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe

installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Releasable Cable Tie, 15.4" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 175.0 lbs

Minimum Tensile Strength (N) 780.0 N

Length L (imperial) 15.4 "

Length L (metric) 390.0 mm

Width W (imperial) 0.35 "

Width W (metric) 8.8 mm

Cable Tie Width Max (imperial) 0.35 "

Cable Tie Width max. (metric) 8.8 mm

Bundle Diameter min (imperial) 0.32 "

Bundle Diameter min (metric) 8.0 mm

Bundle Diameter max (imperial) 4.1 "

Bundle Diameter max (metric) 105.0 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 1000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature $-40 \,^{\circ}\text{F}$ to +185 $^{\circ}\text{F}$ (-40 $^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$)

ROHS Conformity Yes