

## RT250I9X2



**Article Number:** 131-75219

**Releasable Cable Tie, 28.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg**



### Base Data

**Local Order Number** RT250I9X2

**Type** RT250I

**Color** Natural (NA)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
  - Head design provides high tensile strength with very low insertion force even after repeated use.
  - Buckle feature on head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Fixation Method (FF)** None

**Identification Plate Position** none

**Releasable Closure (Yes/No)** Yes

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Short Description** Releasable Cable Tie, 28.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/pkg

### Product Dimensions

**Minimum Tensile Strength (imperial)** 250.0 lbs

**Minimum Tensile Strength (N)** 1115.0 N

**Length L (imperial)** 28.7 "

**Length L (metric)** 730.0 mm

**Width W (imperial)** 0.49 "

**Width W (metric)** 12.5 mm

**Cable Tie Width Max (imperial)** 0.49 "

**Cable Tie Width max. (metric)** 12.5 mm

**Bundle Diameter min (imperial)** 0.47 "

**Bundle Diameter min (metric)** 12.0 mm

**Bundle Diameter max (imperial)** 8.0 "

**Bundle Diameter max (metric)** 203.0 mm

**Thickness T (imperial)** 0.0837 "

**Cable Tie Head Height (Metric)** 9.5 mm

**Cable Tie Head Length (metric)** 22.4 mm

**Cable Tie Head Width (metric)** 20 mm

**Cable Tie Head Length (imperial)** 0.88 "

Cable Tie Head Width (imperial) 0.79 "

Thickness T (Metric) 2.2 mm

## Logistics and Packaging

---

**Quantity per** bag  
**Package Quantity** 25  
**Carton Quantity** 500  
**Weight (Metric)** 18.6 kg

## Material and Specifications

---

**Material** Polyamide 6.6 (PA66)  
**Material Shortcut** PA66  
**CSA Certified** No  
**Flammability** UL94 V2  
**Operating Temperature** -40 °F to +185 °F (-40 °C to +85 °C)  
**ROHS Conformity** Yes  
**Certification / Specification** UL  
**UL Listed (US and Canada)** No  
**UL Recognized (US and Canada)** Yes