

RT250L0X2



Article Number: 115-41500

Releasable Cable Tie, 34.7" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

 **RoHS**

Base Data

Local Order Number	RT250L0X2
Type	RT250L
Color	Black (BK)
Features and Benefits	• Special design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength with very low insertion force even after repeated use. • Buckle feature on head allows excess strap to be tucked away after installation.
Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Fixation Method (FF)	None
Identification Plate Position	none
Releasable Closure (Yes/No)	Yes
Tie Closure	plastic pawl
Variant	Inside Serrated
Short Description	Releasable Cable Tie, 34.7" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial)	250.0 lbs
Minimum Tensile Strength (N)	1115.0 N
Length L (imperial)	34.7 "
Length L (metric)	880.0 mm
Width W (imperial)	0.49 "
Width W (metric)	12.5 mm
Cable Tie Width Max (imperial)	0.49 "
Cable Tie Width max. (metric)	12.5 mm
Bundle Diameter min (imperial)	0.47 "
Bundle Diameter min (metric)	12.0 mm
Bundle Diameter max (imperial)	10.0 "
Bundle Diameter max (metric)	254.0 mm

Logistics and Packaging

Quantity per	bag
Package Quantity	25
Carton Quantity	250

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes