

RT250L9X2



Article Number: 131-75419

Releasable Cable Tie, 34.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/plain pkg



Base Data

Local Order Number RT250L9X2

Type RT250L

Color Natural (NA)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
 - Head design provides high tensile strength with very low insertion force even after repeated use.
 - Buckle feature on head allows excess strap to be tucked away after installation.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Releasable Cable Tie, 34.7" Long, 250 lb Tensile Strength, PA66, Natural, 25/plain pkg

Product Dimensions

Minimum Tensile Strength (imperial) 250.0 lbs

Minimum Tensile Strength (N) 1115.0 N

Length L (imperial) 34.7 "

Length L (metric) 880.0 mm

Width W (imperial) 0.49 "

Width W (metric) 12.5 mm

Cable Tie Width Max (imperial) 0.49 "

Cable Tie Width max. (metric) 12.5 mm

Bundle Diameter min (imperial) 0.47 "

Bundle Diameter min (metric) 12.0 mm

Bundle Diameter max (imperial) 10.0 "

Bundle Diameter max (metric) 254.0 mm

Thickness T (imperial) 0.0837 "

Cable Tie Head Height (Metric) 9.5 mm

Cable Tie Head Length (metric) 22.4 mm

Cable Tie Head Width (metric) 20 mm

Cable Tie Head Length (imperial) 0.88 "

Cable Tie Head Width (imperial) 0.79 "

Thickness T (Metric) 2.2 mm

Logistics and Packaging

Quantity per bag
Package Quantity 25
Carton Quantity 25 Pieces
Weight (Metric) 29 kg

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
CSA Certified No
Flammability UL94 V2
Operating Temperature -40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity Yes
Certification / Specification UL
UL Listed (US and Canada) No
UL Recognized (US and Canada) Yes