

## RT250M0UVX2

Article Number: 131-75620

Releasable Cable Tie, 22.3" Long, 250 lb Tensile Strength, PA66UV, Black, 25/pkg



### Base Data

Local Order Number RT250M0UVX2

Type RT250M

Color Black (BK)

- Features and Benefits**
- UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.
  - Special design offers a release feature for quick and easy access to wire bundles.
  - Head design provides high tensile strength with very low insertion force even after repeated use.
  - Buckle feature on head allows excess strap to be tucked away after installation.

**Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Releasable Cable Tie, 22.3" Long, 250 lb Tensile Strength, PA66UV, Black, 25/pkg

### Product Dimensions

Minimum Tensile Strength (imperial) 250.0 lbs

Minimum Tensile Strength (N) 1115.0 N

Length L (imperial) 22.3 "

Length L (metric) 565.3 mm

Width W (imperial) 0.49 "

Width W (metric) 12.5 mm

Bundle Diameter min (imperial) 0.47 "

Bundle Diameter min (metric) 12.0 mm

Bundle Diameter max (imperial) 5.9 "

Bundle Diameter max (metric) 150.0 mm

Thickness T (imperial) 0.075 "

Cable Tie Head Height (Metric) 9.5 mm

Cable Tie Head Length (metric) 22.4 mm

Cable Tie Head Width (metric) 20 mm

Cable Tie Head Length (imperial) 0.88 "

Cable Tie Head Width (imperial) 0.79 "

Thickness T (Metric) 1.9 mm

## Logistics and Packaging

---

<b>Quantity per</b>	bag
<b>Package Quantity</b>	25
<b>Carton Quantity</b>	500
<b>Weight (Metric)</b>	13 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 UV-resistant (PA66UV)
<b>Material Shortcut</b>	PA66UV
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40 °F to +185 °F (-40 °C to +85 °C)
<b>ROHS Conformity</b>	Yes
<b>Certification / Specification</b>	UL
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	No