

RT250XL0X2



Article Number: 131-75510

Releasable Cable Tie, 40.6" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg



Base Data

Local Order Number RT250XL0X2

Type RT250XL

Color Black (BK)

- Features and Benefits**
- Special design offers a release feature for quick and easy access to wire bundles.
 - Head design provides high tensile strength with very low insertion force even after repeated use.
 - Buckle feature on head allows excess strap to be tucked away after installation.

Product Description HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Fixation Method (FF) None

Identification Plate Position none

Releasable Closure (Yes/No) Yes

Tie Closure plastic pawl

Variant Inside Serrated

Short Description Releasable Cable Tie, 40.6" Long, 250 lb Tensile Strength, PA66, Black, 25/pkg

Product Dimensions

Minimum Tensile Strength (imperial) 250.0 lbs

Minimum Tensile Strength (N) 1115.0 N

Length L (imperial) 40.6 "

Length L (metric) 1030.0 mm

Width W (imperial) 0.49 "

Width W (metric) 12.5 mm

Bundle Diameter min (imperial) 0.47 "

Bundle Diameter min (metric) 12.0 mm

Bundle Diameter max (imperial) 12.0 "

Bundle Diameter max (metric) 305.0 mm

Thickness T (imperial) 0.0837 "

Thickness T (Metric) 2.2 mm

Logistics and Packaging

Quantity per bag

Package Quantity 25

Carton Quantity 250 Pieces

Weight (Metric) 37 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
CSA Certified	No
Flammability	UL94 V2
Operating Temperature	-40 °F to +185 °F (-40 °C to +85 °C)
ROHS Conformity	Yes
Certification / Specification	UL
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	Yes